


Location:



Tub-Shower System 3502-CYL

Specification Submittal



Feature Highlights

- Symmons Tub-Shower System with Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless escutcheon with colored lettering
- Cylinder (CYL) style lever handle
- Showerhead, single mode 352SH
- Mounting bracket and flange for showerhead
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available
- Tub-spout with diverter, 5-1/2 inches #054
- Polished chrome finish (standard)

Model Numbers

- 3502-CYL
Tub-Shower System with Symmons Temptrol® mixing valve, p/n 46-2-BODY
- 3502-CYL-TRM
Trim only, valve must be ordered separately
- 46-2-BODY
Symmons Temptrol® mixing valve without trim
- 46-2X-BODY
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number

- Polish chrome (standard finish)

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Options / Modifications

Append appropriate -suffix to model number

- IPS IPS connections: 1/2 inch female IPS connections on Temptrol® mixing valve
- X Service Stops: Temptrol® mixing valve includes integral service stops to allow water shut-off for service, p/n 46-2X-BODY (Option applies when ordering model 3502-CYL)
- CHKS Check Stops: Temptrol® mixing valve includes integral check stops
Note: Requires integral service stop option (-X) *Used in installations where a positive shut-off device is used downstream of mixing valve*
- REV Reverse core: Temptrol® mixing valve with reverse core. *Used in back-to-back system installations. HOT on the right, COLD on the left*
- 2.0 Flow rate restrictor, 2.0 gpm (7.6 L/min)
- 1.5 Flow rate restrictor, 1.5 gpm (5.7 L/min)
- L/HD Showerhead not included, Mounting bracket and flange are included
- 352SH-3 Showerhead is three-mode in place of standard single mode
- SS Diverter tub spout #053, slip-on type 5-1/2"
- 067 Tub spout without diverter #067, 7 inches
- B Metal escutcheon
- ETCH Escutcheon with black & white lettering

Handle Options / Modifications

Append appropriate -suffix to model number



- LR Lever handle
- LP Loop style lever handle

Dimensions Tub-Shower System, 3502-CYL

