



SYMMONS® Oxford™

Hand Shower System 4203

Specification Submittal

Feature Highlights

- Symmons hand shower system with lever handles.
- Symmons Temptrol® pressure balancing mixing valve with adjustable stop screw to limit handle turn.
- Wall/hand shower with 5 foot flexible metal hose, in-line vacuum breaker, wall connection and cradle for hand shower mounting
- Flow rate 2.5 gpm (9.5 L/min)
- Metal construction with polished chrome finish



Model Numbers

- ☐ 4203Hand Shower System with Symmons Temptrol® pressure balancing mixing valve p/n 4000-BODY
- ☐ 4203-TRMTrim only, valve must be ordered separately
- ☐ 4000-BODY Symmons Temptrol® pressure balancing mixing valve without trim
- ☐ 4000-X-BODY ...Symmons Temptrol® pressure balancing mixing valve without trim. Valve includes integral service stops to allow water shut-off for service.

Finish Options

Append appropriate -suffix to model number.

- ☐ STN Satin nickel finish
- ☐ ORB Oil rubbed bronze finish



Options / Modifications

Append appropriate -suffix to model number.

- ☐ -IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- ☐ -X Symmons Temptrol® pressure balancing mixing valve includes integral service stops to allow water shut-off for service, p/n 4000-X-BODY. (Option only applies when ordering model 4203.)

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations.
- 5 years - for commercial installations

Dimensions *Oxford Hand Shower System, 4203*

