



4087-03

Zinc Rich Cold Galvanizing is highly resistant to all forms of corrosion. Through galvanic action, small scratches "heal" themselves. Perfect where factory galvanized finish is damaged in shipment, assembly, welding, etc. Blends well with hot-dip coating. Forms a zinc film that by electro-mechanical reaction literally fuses itself to iron, steel, and aluminum.

**DIRECTIONS FOR USE:**

Shake can for a full sixty (60) seconds after rattling of mixing ball begins. If application is to cover a large area, periodically shake can to insure uniform mixing of the contents. Surface to be sprayed should be clean and dry. Remove protective cap and point opening in spray nozzle towards surface to be sprayed. Holding can 10 to 12 inches from the surface using a sweeping motion, apply in thin, even coats until surface is completely covered.

**DANGER**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging the unborn child.

**PREVENTION:** Keep away from heat/sparks/open flames/hot surfaces-no smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe gas. Sensitive to static discharge. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**RESPONSE: If on skin:** Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **If inhaled:** Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. **If swallowed:** Call a poison center/doctor if you feel unwell. Rinse mouth. **If exposed or concerned:** Get medical advice/attention.

**STORAGE:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up. **KEEP OUT OF REACH OF CHILDREN.**

**DISPOSAL:** Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains: Liquefied petroleum gas (CAS# 68476-86-8), toluene (CAS# 108-88-3), zinc (CAS# 7440-66-6), and petroleum distillates (CAS# 64742-47-8).

Made in the U.S.A.

Manufactured for:  
Nu-Calgon Wholesaler Inc.  
2008 Altom Court  
St. Louis, MO 63146  
800-554-5499

(815) Calgon is a licensed trade name.

After spraying, turn can upside down and spray until no more zinc is evident. This product is best applied at room temperature (70-80°F). Coating should be touch dry in 15 minutes. May be painted over after allowing approximately six hours to dry. Cures in 24 to 48 hours.

**TYPICAL USES:**

Rust-proofing all welds, air conditioning and heating ducts, sumps, iron, pipes, structural steel work and fan blades, chemical and oil refineries, farm equipment, sign equipment, and anywhere metal is subject to corrosion and rust. Does not contain pvc monomer.


**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects, and other reproductive harm. Metallic Coatings (MCP) Do Not Exceed 80% VOC or 1.90 MIR.



# Zinc Rich

**COLD GALVANIZING COMPOUND**

*Highly Resistant to Corrosion*



**Perfect for Repairing  
Factory Galvanized Metal**

**DANGER:**  
EXTREMELY  
FLAMMABLE.  
VAPOR HARMFUL.  
HARMFUL OR FATAL  
IF SWALLOWED.  
CONTENTS UNDER  
PRESSURE.

KEEP OUT OF REACH  
OF CHILDREN.  
See back panel for  
additional precautionary  
statements.

**FOR PROFESSIONAL  
USE ONLY**

www.nucalgon.com

**NET WT. 13 OZ. (368 GRAMS)**