Models: 47713L









DESCRIPTION

- Metal construction with various finishes identified by suffix
- · Predrilled lift rod hole no waste assembly
- · 1/2" IPS connections
- Will accept standard cone/bevelled connection for 3/8" tubing
- · Six (6) individual boxes per master carton

OPERATION

- · Pivot action, lever-style handle
- · Temperature control by 90° arc
- · International red/blue markings

FLOW

Flow is limited to 1.5 gpm max. (5.7L/min) at 60 psi, for products made before October 2008 flow is limited to 2.2 gpm max. (8.3L/min)

CARTRIDGE

- · Ceramic disc technology
- · Non-metallic, non-ferrous, and plastic material
- · Single body construction for easy replacement

STANDARDS

- All CFG products are compliant to all plumbing codes that require third party certification to the applicable plumbing/fitting standards
- WaterSense® CSA B125.1, ASME A112.18.1, ICC A117.1, ANSI/NSF 61/9 and all applicable requirements referenced therein
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

WARRANTY - RESIDENTIAL, COMMERCIAL

- One year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information