Material: CPVC

Part No: 4235-130 FlameGuard® Brass Transition Fittings

Desc: 1X1/2 CPVC FS FEM SPRINKLER HEAD ADAPTER

MSRP: 13.05 **Part Code:** 076

Weight(lbs): 0.161 Weight(kg): 0.073 Weight(gm): 73

Connection Socket x Brass Fipt


Type Reduction

Color: ORANGE

NOTE Not intended To Convey Or

Dispense Water For Human Consumption Through Drinking

Or Cooking



Size: 1"X1/2"

L = 2-11/32

 $\mathbf{M} = 1-11/16$

M1 = 1-3/16

 $\mathbf{N} = 5/8$

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/32$ inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; $\pm 1/32$ inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/32$ inch


L = Overall length of fittings; $\pm 1/16$ inch.


M = Outside diameter of socket/thread hub; $\pm 1/16$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.


W = Height of cap; $\pm 1/16$ inch

Typical Molded Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006