

Count on total performance from **PRO-LINE™** MAPP® & Propane tips.  
*Varying size tips help you get the job done - quick and easy!*



### PRO-LINE Tips

TIP NO.	TIP SIZE		AIR		COPPER TUBING SIZE CAPACITY PROPANE GAS				COPPER TUBING SIZE CAPACITY MAPP® GAS				REPLACEMENT	
	IN.	MM	@24 PSI LBS/HR	AIR MAPP® @42 PSI LBS/HR	SOFT SOLDER		SILVER SOLDER		SOFT SOLDER		SILVER SOLDER		ORIFICE MODEL	TIP ENDS
					IN.	MM	IN.	MM	IN.	MM	IN.	MM		
PL-3T	3/8	9.5	.33	.46	V <sup>1</sup>	6-25	1/8-1/2	3-10	V <sup>v</sup> 2	10-40	1/4-1/2	6-15	OR-T-3	3T-TE
PL-4T	7/16	11.1	.52	.69	V <sup>1/2</sup>	10-40	1/4-3/4	6-15	1/4-2 1/2	10-60	V <sup>1/4</sup>	6-35	OR-PL4T	4T-TE
PL-5T	5/8	15.9	.71	1.41	H/2-2 1/2	40-60	V <sup>2</sup> -N/4	15-35	1-4	25-100	V <sup>2-2</sup>	15-50	OR-PL5T	5T-TE

**Soldering & Brazing sizes based on Propane. Capacity larger on MAPP® gas.**



**"Total LP" Hose**  
**H-12(1412-0080)**  
**H-24 (0386-1087)**

3/16" I.D.T Grade hose with 9/16" 18 LH Thread. Fits H-4 handle, T-8 torch, R-LP adjustable LP regulator. H-12, 12ft. (3.6m) hose H-24, 24ft (7.3m) hose



**H-4 Handle**  
**(0386-0300)**

Ergonomically designed handle with valve rear and quick disconnect. Fits all Proline and TurboTorch tips. "B" size 9/16"-18 hose connections.



**R-LP Regulator**  
**(0386-0705)**

Brass regulator for use with MAPP, Propane and other LPG fuel gas. Adjustable to 60psi. Fits standard POL valve & 9/16" 18 LH hose nut. Not for use with Acetylene. R-LP-993 Regulator for British 993 Markets, Part No. 0386-0328