Standard ROMAX® Features

pipetool technologies at work



Technical Specifications

	PRESSLINER	AC ECO
Pressing Force:	7,200 lbs (32kN)	7,200 lbs (32kN
Motor:	12V, 2A	110V, 50/60 Hz
Crimping time:	8 sec.	7 sec.
Machine weight: (Incl. battery)	10.8 lbs	11.3 lbs
Dimensions: (L x W x H)	16" x 3" x 6.5"	16" x 3" x 6.5"
Cord length:	n/a	16.4 ft
Switch system:	Quadro (4)	Duo (2)
Cycles before calibration:	10,000	Annually or 10,000 Cycles
Jaw weight: (1/2"-2")	4 to 9 lbs	4 to 9 lbs
Jaw rotation:	270 degrees	270 degrees

Ordering Information

Press Tool Packages




Description	Part	No
PRESSLINER, charger, 2 batteries, carry case	15	422
PRESSLINER, 1/2", 3/4", 1" jaws, charge 2 batteries, carry case	er, 15	423
PRESSLINER, 1/2", 3/4", 1", 1-1/2", 1-3/4 2" jaws, charger, 2 batteries, case	4", 15	424
AC FCO carry case	15	706




AC ECO, carry case	15706
AC ECO, 1/2", 3/4", 1" jaws, carry case	15720
AC ECO, 1/2", 3/4", 1", 1-1/2", 1-3/4", 2" jaws, carry case	15721

Accessories











Carry Case PRESSLINER and AC ECO	F81664
Carry Case for 6 jaws (holds 1 ea. of 1/2", 3/4", 1", 1-1/2", 1-3/4", 2")	15031

Related Products




MINICUT II PRO, 1/4" - 7/8" OD	70402
Tube Cutter 35 PRO, 1/4"- 1-3/8" OD	70027
Automatic Tubing Cutter, 1/8" - 2-5/8" OD	70030



-	Automatic Tubing Cutter, 1/8" - 2-5/8" OD	70030	
	Universal Internal/External Deburring Tool, 1/8" - 1-3/4" OD	70075	

Deburring Tool with Machinist Reamer





ROTHENBERGER USA LLC 4455 Boeing Drive Rockford, IL 61109 rothenberger-usa.com

© ROTHENBERGER USA 2007 R0045 Rev.03/07





