

Compact Threading Machines

Product Profile

FEATURES

- Motor double insulated:
- Stable high torque motor: Constant power
- Offset spindle lubrication:
- Easy to maintain
- Geared oil pump with filter system and adjustable fluid level: Constant oil flow
- Large plastic chip collection tray:
- Easy to clean
- Machine slightly angled:

Reduced oil consumption, oil moistening in pipe interior is avoided

TECHNICAL DATA

dia. 1/4" - 2" NPT: 750 watts (1 HP) Motor Strength: Speed: 40 rpm (No load)

21" x 17" x 13" (L x W x H) • Dimensions:

Optional

• Wheeled folding stand (56051) Can be used anywhere; provides storage





ROPOWER 50R

The ROPOWER 50R uses RIDGID®*-compatible dies with the new quick-change ball detent feature. While other manufacturers' RIDGID®* style dies may be used in the 50R die head (56265), only ROTHENBERGER's dies snap into position.

Standard Supply: ROPOWER 50R, Automatic die head 1/2"-2" (56265), alloy NPT dies (1/2"-3/4" 89162 and 1"-2" 86163, set of 4 legs, safety foot switch, 1 gallon ROCOOL® oil (01922)

Description	↓ lb	No.
ROPOWER 50R with Automatic die head with NPT Alloy dies 1/2"-2"	97.0	63005
Wheeled folding stand	70.0	56051
Mounting kit for ROGROOVER	4.0	56511
Cutter Wheel		04510

50R Die Head & Die Selection Chart **RIDGID®** Compatible Dies Die Head Die Head **NPT Die** Alloy High Speed Stainless Size Steel No. Type Size Nο No. Steel 56265 1/2"-3/4" 89162 00125 00218 **Automatic** 1/2" – 2" 1"-2" 00126 00219 89163 1/4"-3/8" 00121 1/4"-3/8" 56383 Manual