

Threading Accessories

3

Pipe Threading and Grooving



65008



65013

RONOL®

High-performance cutting oil

Mineral oil basis

For threading of all materials, including stainless steel

Mineral-based threading oils may not be permissible in drinking water installations
Please check the pertinent standards in your area.

Description	Contents	lb	No.
RONOL® Spray	6.8 oz. (200 ml)	0.6	65018
RONOL® Spray can	20.3 oz. (600 ml)	1.7	65008

RONOL® SYN

High-performance cutting fluid

No mineral oils, purely synthetic:

Developed and approved for drinking water and plumbing installations.

Description	Contents	lb	No.
RONOL® SYN Spray can	20.3 oz. (600 ml)	1.7	65013



01922

00002

ROCOOL® Cutting Oil

Special blend of sulfo-chlorinated mineral oil assures long die life and superior quality threads. ROCOOL® cutting oil and automatic through-the-die-head oil flow makes it impossible to cut a dry thread.

Description	lb	No.
ROCOOL® Cutting Oil (1 gallon)	8.0	01922
ROCOOL® Cutting Oil (six 1 gallon containers)	48.0	00001
ROCOOL® Cutting Oil (5 gallons)	40.0	00002
ROCOOL® Cutting Oil (55 gallons)	480.0	00003
ROCOOL® Cutting Oil Pallet of 1 gallon containers		00001P



Safety Foot Switch

For all ROTHENBERGER threading machines.

Corresponds to industrial associations' safety and accident requirements, with oil-proof rubber cable and plug.

Model	lb	No.
3 step, with emergency stop switch, 115V	5.0	00161