

# TOTO®

# CT418F(G)

## Aquia® Wall-Hung Dual-Flush Toilet, 1.6 GPF & 0.9 GPF

### FEATURES

- Dual-Max® flushing system, high efficiency (1.6 GPF/6.0 LPF & 0.9 GPF/3.4 LPF)
- Optional CEFIONTECT® ceramic glaze - prevents debris, mold from sticking to ceramic surfaces, leading to fewer chemicals and less water in cleaning.
- Universal Height
- Wall-hung toilet can be paired with TOTO in-wall tank system as well as others

### MODELS

- CT418FG#01 - with CEFIONTECT
- CT418F#01 - without CEFIONTECT
  
- SS204 SoftClose® seat (sold separately)
- SS114 SoftClose seat (sold separately)
- SC134 commercial seat (sold separately)
- SC534 commercial seat (sold separately)
  
- WT171M In-wall tank system (copper pipe) (sold separately)

#### Kit Configurations

- CWT418MFG = WT171M + CT418FG + YT920
- CWT418MF = WT171M + CT418F + YT920

### COLORS/FINISHES

- Standard  
#01 Cotton

### PRODUCT SPECIFICATION

This universal height, low consumption Dual-Max flushing system toilet shall be 1.6 GPF & 0.9 GPF. Toilet shall have optional CEFIONTECT ceramic glaze. Toilet shall be mounted to in-wall tank system, elongated front bowl and wall-mounted push-button type. Toilet shall be TOTO Model CT418F(G)#01.



**D+** Dual-Max

**CEFIONTECT**

### CODES/STANDARDS

- Meets or exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO (cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- Complies with CA Prop 65 warning requirements



# CT418F(G)

## Aquia® Wall-Hung Dual-Flush Toilet, 1.6 GPF & 0.9 GPF

### SPECIFICATIONS

- Water Use 1.6 GPF & 0.9GPF (6.0 LPF & 3.4LPF)
- Flush System Dual-flush
- Min. Water Pressure 8 psi (static)
- Water Surface 5.5" X 4.75"
- Trap Diameter 2-1/8"
- Installation Height 15" to 19"
- Trap Seal 2-1/8"
- Warranty One Year Limited Warranty
- Material Vitreous china
- Shipping Weight CT418F(G) - 66.5 lbs.
- Shipping Dimensions CT418F(G)  
23-3/4" L X 15-3/4"W X 17-1/2" H

### INSTALLATION NOTES

