





Royal Prison 9611 S.S. - Rev. 0b (11/10) Copyright © 2010 SLOAN VALVE COMPANY

Hydraulic Royal® Prison Model Flushometer



Concealed, Hydraulically Activated, Water Closet Flushometer for wall hung stainless steel back inlet bowls.

Flush Cycle

□ Model 9611 Water Saver (3.5 gpf/13.2 Lpf) □ Model 9611-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Closet Flushometer for either left or right hand supply with the following features:

- PERMEX[™] Synthetic Rubber Diaphragm w/Dual Filtered Fixed Bypass
- ADA Compliant Non-Hold-Open Actuator (specify Actuator type listed below)
- 1" I.P.S. Wheel Handle Bak-Chek[™] Angle Stop
- · Adjustable Tailpiece
- High Back Pressure Vacuum Breaker
- Elbow Flush Connection and Coupling for 11/2" NPT Back Inlet (for connection in the pipe chase — flush connection through the wall not provided by Sloan)
- · Sweat Solder Adapter
- Exposed Parts Chrome Plated
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Push Button, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID[™] Technology
- Diaphragm, Stop Seat and Vacuum Breaker molded from PERMEX[™] Rubber Compound for Chloramine Resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources - Wind Energy

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Actuator Types: (please check one)

□ MBFW Metal Button Fixture Wall Actuator (HY-100-A) (rear access)

Variations

Shorter Vacuum Breaker - for use with Anti-Flood Device (Anti-Flood Device NOT provided by Sloan) Trap Primer Elbow

Less Vacuum Breaker



This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	

The information contained in this document is subject to change without notice



SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com



certificates to meet 100% of the company's purchased electricity use at its Franklin Park, Illinois facility.