

# Tubular Brass

Model 501/502-NY

Model 551/552-NY

With New York Lay-Down Tee

**Sturdy 1.5" 17g and 20g Tubular Brass  
Slip-Joint Assembly**

## SPECIFICATIONS

### FEATURES:

- New lay-down tee allows both above-the-floor and through-the-floor installations.
- Extended drain allows tee to be installed either way without sacrificing adjustability.
- Designed for heavy-duty use in hotels, motels, and rental properties.
- Available on all Watco brass bath wastes; just add "NY" to the item number.
- Includes three brass slip nuts and slip joint washers; does not include a tailpiece.
- Retainer plate for overflow ell.

### APPROVALS (501/502, 551/552):

- IAPMO (UPC) approved, File 2255.
- Complies with ASME A112.18.2-2005/ CSA B125.2-05, TIL MSE-051.

### PATENTS:

- See <http://watcomfg.com/Watco/patents/> for Details

### THREAD SIZE (Strainer Body and Drain Elbow):

- 1½" – 11½" NPSM (Coarse Thread)
- 1.865" Major Diameter (outside thread diameter)
- 11.5 threads per inch

### PIPING:

- 17g: 501/551 models      □ 20g: 502/552 models



### OPTIONS:

- Brass Ferrules (add code "F" to part number)
- Slip-'N-Solder (no compression slip joints), Code "U"
- Special lengths available:
  - Overflow extension (add code "EXlength") example: EX6
  - Drain extension (add code "Dlength") example: D4



**ADA**

PRESFLO® (PF) and  
Foot Actuated (FA) only

See price list for complete item numbers and available options.

When ordering, please specify complete item number  
and any applicable option codes.



For More Information Contact:  
**WATCO Manufacturing Company**  
1220 South Powell Road  
Independence, MO 64057-2724  
Ph. 816-796-3900 • FAX 816-796-0875  
[www.watcomfg.com](http://www.watcomfg.com)

