WOODFORD

The Woodford Model 25 drains as handle is shut off <u>even</u> <u>if hose is attached</u>. This faucet is designed for outside residential water service applications and intended for irrigation purposes.

SPECIFICATIONS:

MODEL 25 - Approved under ASSE Standard 1019-B and listed by IAPMO®. MeetsGovernment Specification WW-541b Type 205.

Vacuum Breaker - Anti-Siphon

NIDEL® model 34HA with 3/4" male hose thread. Approved under ASSE Standard 1011. Canadian Standards Association and listed by IAPMO®. FEATURES:

EXTERIOR FINISH - Brass

VALVE - Molded nitrile suitable for hot water.

NOZZLE - 3/4" male hose thread.

NO LEAD SOLDER - All solder joints.

PLUNGER - Hemispherical cushion type.

STEM SCREW - DELRIN®

HEAD NUT - Brass


HANDLE - Metal. (Optional Tee Key)

INLETS - As shown.

MAX PRESSURE - 125 p.s.i.

MAX TEMPERATURE - 120° F

NOTICE - To close and drain, turn handle clockwise until seated and water drains out of the drain hole or faucet may freeze and burst. Vacuum Breaker replacement is recommended every 3-5 years.



 2.0
 2.1
 2.2
 2.3
 2.4
 2.5
 2.7
 2.9
 3.1
 3.3

 Shipping Wt. (lbs)
 Approx. Shipping Weight Each


*Overall Length Dimension: Add wall thickness and inlet option length shown in chart at right.


For Installation / Troubleshooting Instructions go to www.woodfordmfg.com or call 1-800-621-6032


Anti-Siphon Automatic Draining Freezeless Wall Faucet Model 25




Inlet Descriptions









C Inlet COMBINATION Copper Sweat Fitting 1/2" K, L or M Inside 3/4" M Only Outside

CP Inlet COMBINATION 1/2" Male Pipe Thread 1/2" Female Sweat

CP3 Inlet COMBINATION 3/4" Male Pipe Thread 3/4" Female Sweat

P Inlet COMBINATION 1/2" Female Pipe Thread 3/4" Male Pipe Thread

PX Inlet 1/2" PEX Tube Fitting PX3 INLET 3/4" PEX Tube Fitting

When ordering, specify model, inlet and wall thickness.

Rev. 07/16 Form No. 25.107