

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, assuring consistent, optimum quality in every fastener.

### FASTENER TERMINOLOGY SUFFIX

K = Knurled	X = Collated	C = 100 count
B = Black	SD = Washer	M = 1000 count
E = Ramguard	TH = Top Hat	

## SELECTION CHART

### BLACK TRACK PINS

Designed for use in concrete and structural steel applications. Available in 100-pack or 1000-pack per box.



PART NUMBER	SHANK LENGTH		721/ R25	ROCKET	D60/D45A	SA270	XT540	COBRA	MASTERSHOT/ RS22	Master Carton Qty
	IN.	(MM)								
1506B	3/4	(19.1)	•	•	•	•	•	•	•	5000

Shank diameter = .145 Head diameter = .300

### PLATED PINS

Designed for use in concrete and structural steel applications. 100 per box.



PART NUMBER	SHANK LENGTH		721/ R25	ROCKET	D60/D45A	SA270	XT540	COBRA	MASTERSHOT/ RS22	Master Carton Qty
	IN.	(MM)								
1503K	1/2 Knurled	(12.7)	•	•	•	•	•	•	•	5000
1506	3/4	(19.1)	•	•	•	•	•	•	•	5000
1508	1	(25.4)	•	•	•	•	•	•	•	5000
1510	1-1/4	(31.8)	•	•	•	•	•	•	•	1000
1512	1-1/2	(38.1)	•	•	•	•	•	•	•	1000
1514	2	(50.8)	•	•	•	•	•	•	•	800
1516	2-1/2	(63.5)	•	•	•	•	•	•	•	800
1524	3	(76.2)	•	•	•	•	•	•	•	600

Shank diameter = .145 Head diameter = .300

### WASHERED PINS

Washer increases bearing surface against the material to be fastened. 100 per box. 16 gage metal washer. 7/8" diameter washer.



PART NUMBER	SHANK LENGTH		721/ R25	ROCKET	D60/D45A	SA270	XT540	COBRA	MASTERSHOT/ RS22	Master Carton Qty
	IN.	(MM)								
1506SD	3/4	(19.1)	•	•	•	•	•	•	•	1000
1508SD	1	(25.4)	•	•	•	•	•	•	•	1000
1510SD	1-1/4	(31.8)	•	•	•	•	•	•	•	1000
1512SD	1-1/2	(38.1)	•	•	•	•	•	•	•	1000
1514SD	2	(50.8)	•	•	•	•	•	•	•	1000
1516SDC	2-1/2	(63.5)	•	•	•	•	•	•	•	600
1524SDP*	3	(76.2)	•	•	•	•	•	•	•	600

\*Square washer indicates 3" pin has been installed Shank diameter = .145 Head diameter = .300

### RAMGUARD PINS

Coated to improve corrosion resistance in treated lumber and other applications. 100 per box. Recommended for treated lumber applications.



PART NUMBER	SHANK LENGTH		721/ R25	D60/D45A	ROCKET/ SA270	XT540	COBRA	MASTERSHOT/ RS22	Master Carton Qty
	IN.	(MM)							
1516E	2-1/2	(63.5)	•	•	•	•	•	•	800
1516SDE	2-1/2	(63.5)	•	•	•	•	•	•	600
1524SDE*	3	(76.2)	•	•	•	•	•	•	600

Shank diameter = .145  
Head diameter = .300

\*Square washer indicates 3" pin has been installed

\* 1500 Series Coated with RamGuard