


## Light and mirror Mirror with lighting # LM7826

|< 31 1/2" Inch >|



| Mirror with lighting   | Dimension                               | Weight | Order number |
|--|---|--------|--------------|
| "Premium" - Version, cIAPMO®ELECTRICAL, LED ar<br>(4 sided), 1 sensor switch bottom right, de-fogging<br>dimming function, Mirrors require a GFCI 110 V 60 l<br>source. Flat plug will be supplied with mirror, LED (<br>30,000 hours), LED module permanently enclosed, | system, ĹED<br>Hz power<br>(life span > |        |              |
| 4000 kelvin light color, 68 W  |   |        |              |
| Colors   |   |        |              |
|  |   |        |              |
| Variant  |   |        |              |
|  | 31 1/2" x 1 1/4" Ir                     | nch    | LM7826       |
| Infobox  |   |        |              |
| # LM 7825, LM 7826, LM 7827 and LM 7828 are available from stock, Distance between sensor and reflecting surfaces = minimum 3", Sensor controls both light and heater  |   |        |              |
|  |   |        |              |
|  |   |        |              |
|  |   |        |              |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.