Cordless > 18v LXT[®] Lithium-Ion > **FASTENING / ACCESSORIES**

POWERFUL DISPENSING FORCE



18v LXT® 10 OZ. CAULK/ADHESIVE GUN KIT

Delivers an Industry-Leading 1,100 lbs. of Dispensing Force

- · Makita-built motor delivers 1,100 lbs. of dispensing force to dispense the highest viscosity adhesives and sealants
- · 5-speed dial optimizes flow rate from 0-66 IPM · Variable speed trigger allows user match speed to
- the application 360° rotatable cartridge holder fits 10 oz. and 300 ml
- cartridges

Model XGC011 Includes: 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XGC01Z Includes: Tool Only: Battery and Charger not included

Capacity (caulk or sealants)	10 oz.
Dispense Force	1,100 lbs.
Inches Per Minute (variable speed)	0 - 66 IPM
Speed Settings	5
Battery	18V LXT® Lithium-Ion
Overall Length	15-7/8"
Net Weight (with battery)	5.1 lbs.

Caulking Gun

Accessories

XGC011B

3.0A

P

18v LXT[®] 20 OZ. CAULK GUN KIT Delivers Up To 2.5X More Dispensing Speed

3.0

12.01 lbs.

makite

· Makita-built motor delivers 1,100 lbs. of

- dispensing force to dispense the highest viscosity adhesives and sealants
- · 5-speed dial optimizes flow rate from 0-66 IPM
- · Variable speed trigger allows user match speed to the application
- · 360° rotatable cartridge holder fits 20 oz. cartridges, sausage packs and bulk caulk and adhesives
- · Includes 3 pistons for use with cartridges, sausage packs and bulk materials

Model XGC011B Includes: 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC)

	Model XGC01ZB Includes: Tool Only; Batte	ery and Charger not included
	Capacity (caulk or sealants)	20 oz.
	Dispense Force	1,100 lbs.
1	Inches Per Minute (variable speed)	0 - 66 IPM
5	Speed Settings	5
ı	Battery	18V LXT® Lithium-Ion
	Overall Length	21-1/4"
	Net Weight (with battery)	6 lbs.

3 Compared to leading competitor

Shipping Weight

12/1

DCF300Z



18v LXT® 29 OZ. **CAULK AND ADHESIVE GUN KIT** Delivers an Industry-Leading 1,100 lbs.

of Dispensing Force

- · 5-speed dial optimizes flow rate from 0-66 IPM · Variable speed trigger allows user to match speed to the application
- · 360° rotatable cartridge holder fits 29 oz. cartridges · Drip-reduction feature automatically relieves pressure on the material when trigger is released to prevent
- unintentional dispensing Overload indicator light notifies the operator when tool is nearly overloaded to minimize breakage of the
- sealant cartridge

Model XGC01M1C Includes: 18V LXT[®] Lithium-Ion 4.0Ah Battery (BL1840B), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Holder C (455951-6), Holder Joint C (143223-8), Piston D (143221-2), Rod (143220-4), Tool Bag Model XGC01ZC Includes: Tool Only; Battery and Charger not included

Tnakita

Capacity (Caulk of Scalarits)	29 02.
Dispense Force	1,100 lbs.
Inches Per Minute (variable speed)	0 - 66 IPM
Speed Settings	5
Battery	18V LXT® Lithium-Ion
Overall Length	18-7/8"
Net Weight (with battery)	5.9 lbs.
Shipping Weight	14 lbs.

18V LXT[®] FANS & BLOWER



Tool only - battery and charger not included

18v LXT® JOB SITE FAN Up to 5.5 Hours of Continuous Run

- site environment
- · Two settings (high 1,700 RPM, low 1,200 RPM) for
- · 3-stage automatic timer with 1, 2, and 4 hour power-
- nq
- range of fan

ge	14.4-18V
daptor	Yes
d (2 speed)	0 - 1,700, 0 - 1,200 RPM
lime (max, in hours)	5.5
ry	18V LXT® Lithium-Ion
nsions (LxWxH)	5" x 13-3/5" x 21-1/10"
Veight (with battery)	5.7 lbs.
bing Weight	7.1 lbs.



DUB182

18v LXT® BLOWER KIT 179 MPH for Fast Clean-Ups

- · Variable speed (0-18,000 RPM) for optimum speed control
- · Up to 12 minutes of continuous operation at high speed with a 3.0Ah LXT® battery
- · Compact and ergonomic design at only 20-3/4" long · Weighs only 3.9 lbs. with battery for reduced operator fatique
- · Rubberized soft grip handle for increased operator comfort · Makita-built variable 3-speed motor produces a
- maximum air velocity of 179 MPH Model DUB182 Includes: 18V I XT® Lithium-Ion 3 0Ah

Battery (BL1830), 18V Lithium-Ion Rapid Optimum Char (DC18RC), Rubber Blower Nozzle (132025-7), Tool Bag Charger Model DUB182Z Includes: Tool Only; Battery and Charger not included

Air Volume	91 CFM
Max. Air Velocity	179 MPH
No Load Speed (variable speed)	0 - 18,000 RPM
Battery	18V LXT® Lithium-Ion
Net Weight (with battery)	3.7 lbs.
Shipping Weight	11 lbs.

196352-6

196351-8

and adhesives

10 oz. Cartridge Holder Set

Holds 10 oz. cartridge style caulks

20 oz. Barrel Holder Set Holds 20 oz. cartridge style, sausage style and bulk caulks and adhesives



29 oz. Cartridge Holder Set Holds 29 oz. cartridge style caulks and adhesives

12/1 Tool only - battery and **BCF201Z** charger not included 18V LXT[®] 13" JOB SITE FAN

Up to 5.7 Hours of Continuous Run-Time on a Single Charge⁴

- Durable design engineered to withstand a job site environment
- · Frame structure engineered to reduce wind noise
- · Three settings (high/medium/low) and oscillation selector for optimal air velocity and control
- 3-stage automatic timer with 1, 2, and 4 hour poweroff selection
- · Removable front guard for convenient clean up
- · Tilt up/down design make it convenient to redirect air flow

Model DCF300Z Includes: AC Adapter; Battery and Charger not included

Voltage	18V
AC Adaptor	Yes
Run Time (max, in hours)	5.7
Battery	18V LXT® Lithium-Ion
Dimensions (LxWxH)	12-1/2" x 18-9/10" x 23-7/10"
Net Weight (with battery)	10.4 lbs.
Shipping Weight	12.6 lbs.
⁴ In low speed using a BL1850 batte	ery

makitatools.com

Run T

Batte

Dime

Net W

Shipp

- Time on a Single Charge · Durable design engineered to withstand a job
- · Protective bumpers for increased durability
- optimal air velocity control

Battery and

	Model BCF201Z Includes: AC Charger not included	Adapter
8V	Voltage	
/es	AC Adaptor	
57	Speed (2 speed)	0 - 1,

	off selection
•	Large carrying handle for easy handlir
	45° adjustable platform allows a full rapositions
	Model BCF2017 Includes: AC Adapter: