Pneumatics > HIGH PRESSURE / NAILERS



ADVANTAGES OF MAKITA HIGH PRESSURE

MORE POWER

High pressure compressor technology delivers 400 PSI

LESS WEIGHT

Nailers are up to 30% less weight than conventional nailers

BETTER PERFORMANCE

Dual-head (2-stage) pump compressor provides faster recovery time

INCREASED EFFICIENCY

Low amp draw reduces tripped breakers and voltage drop during start-ups

MORE POWER MORE CONSISTENCY Thakita 🤪

Conventional Nailers ĩ . Engineered Material Drive larger nails (3-1/2" x .162" size) more consistently in engineered materials

DNEUMATICS

AC310H

2.5 HP* HIGH PRESSURE **AIR COMPRESSOR** High Pressure Technology Delivers

400 PSI Capacity

- · Dual capacity: two universal couplers for conventional nailers and two couplers for high pressure nailers
- · Low amp draw reduces incidences of tripped breakers and voltage drop during start-ups
- · Efficient dual-head (2-stage) pump provides faster recovery time and improved performance
- Pump runs at lower RPM (1,720) resulting in lower noise and improved pump durability

Model AC310H Includes: (2) 1/4" High Pressure Universal Quick Coupler, Female (HY00000337), (2) High Pressure Quick Coupler (HY00000351)

	Maximum Horsepower	2-1/2 HP	1
	Running Horsepower	1.9 HP	ľ
	Tank	1.6 gal.	
	Performance: 40 PSI (3.7 CFM), 90 PSI (3.6 CFM), 300 PSI (2.7 CFM)		
	Maximum Pressure	400 PSI	F
	Net Weight	79.4 lbs.	h
	Shipping Weight	88.16 lbs.	



AN930H

3-1/2" HIGH PRESSURE FRAMING COIL NAILER Superior Power-to-Weight Ratio

· Up to 30% less weight (5.7 lbs.) and up to 30% smaller than conventional framing nailers

- "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- 2-mode trigger allows operator to select sequential or contact nailing options
- High capacity canister holds up to 300 nails for high production applications
- High Pressure technology enables nailer to operate at 170-320 PSI for more consistent flush nailing
- Model AN930H Includes: (424390-1), Air Tool Oil (194381-3), Tool Case, Safety Goggles

,	Operating Air Pressure	170 - 320 PSI
,	Nail Size 1-3/4" - 3-1/2" .099"148"	shank diameter wire collated
	Nail Size (in., ga.)	1-3/4" to 3-1/2" (ga.)
	Magazine Capacity (range)	150 - 300
2	Dimensions (LxWxH)	11-1/4" x 5" x 13"
	Overall Length	11-1/4"
	Net Weight	5.7 lbs.
•	Shipping Weight	12.4 lbs.



Tnakita

15°

15°

AN610H 2-1/2" HIGH PRESSURE

SIDING COIL NAILER Delivers Precise Flush Nailing

- Innovative high pressure technology enables nailer to operate at 320 PSI for more consistent flush nailing · "Tool-less" depth adjustment engineered for more
- precise flush and countersink nailing 2-mode selector switch allows operator to select
- sequential or contact nailing options Multi-directional exhaust port directs exhaust air away
- from operator
- · High capacity canister holds up to 400 nails for high production applications

Model AN610H Includes: No-Mar Tip (421574-2), Air Tool Oil (194381-3), Tool Case, Safety Goggles (192517-8)

	Operating Air Pressure		140 - 320 PSI
	Nail Size	1-1/4" - 2-1/2"	.080"113" shank diameter
	Magazine Capacity (rar	nge)	200 - 400
	Dimensions (LxWxH)		11-1/8" x 5-3/8" x 10-7/8"
1	Net Weight		4.2 lbs.
3	Shipping Weight		7.94 lbs.



DNEUMATICS

AN923

3-1/2" FRAMING NAILER

Drives up to 3-1/2" x .162" (16d) Nails · 3-Mode selector switch (contact, sequential, lock)

- allows user control over nailing options · Large capacity air chamber for increased power to
- drive nails varying in length from 2" to 3-1/2" · Built-in air filter minimizes dust and debris from
- entering tool Anti-dry mechanism stops tool when three nails
- remain in the magazine
- · Solid rear-loading aluminum magazine for longer life
- Model AN923 Includes: Pneumatic Nailer Oil (181434-7), Tool Hook (122742-7), Safety Goggles (191687-A), Air Fitting (311006-A)

Operating Air Pressure	65 - 120 PSI
Nail Size 2" - 3-1/2" .113"162" shan	k diameter plastic or wire collated
Magazine Capacity (range)	64 - 74
Dimensions (LxWxH)	22" x 4-1/4" x 13-11/16"
Net Weight	8.7 lbs.
Shipping Weight	12.3 lbs.



DNEUMATICS

21°

AN902 15° **3-1/2" FRAMING COIL NAILER** More Power and Less Weight for

- · "Tool-less" depth adjustment engineered for more

- · Easy loading canister with nail size adjustment provides maximum versatility
- Bubberized handle for better fit and added comfort · Contact mode trigger allows operator to control nailing
- operations

Model AN902 Includes: Pneumatic Nailer Oil (181434-7), Safety Goggles (191687-A), No-Mar Tip (BA00000372)

SI	Operating A	ir Pressure	60 - 120 PSI
ed	Nail Size	1-3/4" - 3-1/2" .099	148" shank diameter wire collated
74	Magazine Ca	apacity (range)	150 - 300
6"	Dimensions	(LxWxH)	12-1/2" x 5" x 14-7/8"
s.	Net Weight		7.7 lbs.
s.	Shipping We	eight	10.1 lbs.



DNEUMATICS

AN611

2-1/2" SIDING COIL NAILER 'Tool-less" Depth Adjustment

- with 9 Settings · "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- · 3-mode selector switch (contact, sequential, lock) allows user control over nailing options
- · Built-in air filter minimizes dust and debris from entering tool
- · Multi-directional exhaust port directs exhaust air away from user
- · Easy-loading canister with nail size adjustment provides maximum versatility

Model AN611 Includes: Pneumatic Nailer Oil (181434-7), Hex Wrench (783202-0), Safety Goggles (191687-A), Air Fitting (311006-A), Tool Case

Operating Air Pressure	65 - 120 PSI
Nail Size	1-1/4" - 2-1/2" .080"099" shank diameter
Magazine Capacity (rang	je) 200 - 400
Dimensions (LxWxH)	13-1/16" x 5" x 12-1/2"
Net Weight	5.1 lbs.
Shipping Weight	10.15 lbs.



High Pressure Accessories

High Pressure Contractor Hose

- Up to 2X less weight than heavier hoses, ideal for trim roofing, framing and construction
- Highly flexible and less kinks for easy rolling and improved air flow
- Engineered to be more durable than vinyl hoses for longer life and improved performance
- flexibility even under extreme weather conditions



*Maximum horsepower

15°

- All-weather resistant, engineered to maintain



PNEUMATICS | 85

- **Increased Versatility** precise flush and countersink nailing
- Drives 1-3/4" to 3-1/2" coil framing nails
- · Easy access nose design for clearing jammed nails