AUTOMATIC EVAPORATIVE COOLER PURGE SYSTEM





Changes cooler water every 8 hours of operation

Every 8 hours of existing cooler pump operation, the Power-Clean® drain pump activates to remove the old cooler reservoir water. The cooler is then refilled with fresh water.



- Saves water and money
 Reduces maintenance

 - Freshens air
 - Pads last longer
 - Prevents mineral buildup

The best way to keep your cooler clean has always been to install a "bleed-off" system which drains off a percentage of water while the cooler is in operation.

Now you can replace the "bleed-off" with a system that can save as much as 3000 gallons of water per month. That is a lot of water in a season.

Power-Clean® will save money and conserve water by automatically flushing your cooler clean every 8 hours of existing cooler pump operation.

Power-Clean® includes...

- Purge pump
- Mesh pump screen


POWER-CLEAN®

Const of Station	Contraction of the second	CHEMISSISSICS, MA.
STATISTICS AND	Course and	CONTRACTOR OF THE OWNER OF THE
SHUMANAL CALS?	CHEAN STRATES	All and a second
CENS, STERES	and the second second	CONTRACTOR OF A DESCRIPTION OF A DESCRIP
	Contraction of the second	Constanting of the second
電話記載 支払 (2)7	1261 School	No. of the second second second
CHARLES IN THE	Carl A Stand	MARTINE ARTIKE

WITHOUT POWER-CLEAN®

CONTRACTOR A PRIME	CARGE ALCONTRACTOR	NAMES AND ADDRESS OF
CB reserves the	Address of the second	Succession in the
e l'accar (actail	A STATE AND A STATE	an antibity many dates
A	- Carana Carata	There is a second of the
ALC: NOT THE OWNER	Later and the second second	and the state of the state
101 - 24 - 25- 161	I COM THE MAN THE REAL	And I wanted the state of the state
Contraction of the second second	A REAL PROPERTY AND	Manufactor Particip
State and state of the	AN AND STORES	CONTRACTOR OF THE

AUTOMATIC POWER-CLEAN®



EASY TO INSTALL

Once installed in the pan of the cooler, Power-Clean® automatically cycles every 8 hours of cooler pump operation to empty the water and replenish the cooler with fresh water.

The cooling capability is never interrupted. Replacing the cooler water on a regular basis is beneficial by removing mineral scale build-up and bacterial growth. Power-Clean® eliminates the need for a bleed-off and the use of cleaners and harsh chemical additives.

> — 30 inches of 1/2 inch I.D. vinyl drain hose — Drain hose to overflow pipe adapter

	Part No.	Description	Amp Rating*	Pkg.	Carton Qty.	Carton Wt.	
(▲ 1540	115V Power-Clean® Kit — Complete kit for all cooler models	0.7	Box	6	16.5	
U PN 1552	▲ 1542	230V Power-Clean® Kit — Complete kit for all cooler models	0.4	Box	6	16.9	

Mounting bracket

Installation instructions

1	Н	
ę	Ż	
1	Ţ	
5	2	λ.

	▲ 1552	Purge Pump Drain Adapter — Adapter only		Clam	6	0.1	
5	▲ 1556	Purge Pump Drain Kit and Overflow Pipe	_	Bag	25	1.6	

PN 1556



FITS ALL EVAPORATIVE COOLERS

*In Tucson, Arizona; a 1.6 amp pump fuse may be required for Power-Clean® operation. POWER-CLEAN® is a registered trademark of Dial Manufacturing, Inc.