

## STEAM SUITE

**AUTO FLUSH STEAM GENERATOR** 

- 1 year in-home warranty
- 2 year at the factory, after in-home
- · Auto flush Pressurized inner tank cleaning system
- Superior incoloy heating elements low watt density
- · Constant steam at a constant rate
- Stainless steel construction
- Integrated drain pan
- · Can be plumbed 50 ft. from the shower
- 50 ft. control cable included
- Sizing is easy L x W x H = Steam Room Cubic Feet



MODEL	INPUT VOLTAGE	KW RATING	AMPS	WIRE	BREAKER	PHASE	MAX. ROOM SIZE
ASD-300A	208-240VAC	8.0	37	8	40	1	175 CU.FT.
ASD-575A	208-240VAC	11	55	6	60	1	395 CU.FT.

Weight: 28 lbs.
Water Inlet: 3/8" NPT

Steam Outlet: 1/2" NPT

Safety Valve: 3/4" NPT Drain Pan: 3/4" NPT

#### **Installation Notes**

Generator is factory sized

- L x W x H = Steam Room Cubic Feet
- Always round up when calculating the total cubic feet.
- Then choose the appropriate generator.
- Ceiling height should not exceed 8 ft.

## Please check date of your Net Price sheet for current pricing

### **CONTROL KITS**

Your choice of either control kit to complete your package



4"w x 2-1/4"h x 3/4"d



1-1/2" x 1-1/4" x1 1/2"

# CONTROL KIT STTC-OSS-XX\*

Available in PC, PN, SN, ORB

#### Control Features:

- 4 adjustable set point temperatures
- Operates auto flush
- Last temperature memory
- 45 minute timer
- All metal construction, not plastic

#### **Deluxe Steamhead**

- Dispenses steam safely
- Aromatherapy well



4-1/2" x 3-9/16" x 3/4"



1-1/2" x 1-1/4" x1 1/2"

#### CONTROL KIT STSC-OSS-XX\*

Available in PC, PN, SN, ORB

#### **Control Features:**

- Day Clock
- Set time
- Set temperature
- Operates auto flush
- Last setting memory
- · All metal construction, not plastic

#### **Deluxe Steamhead**

- Dispenses steam safely
- Aromatherapy well

\*Select desired finish and replace XX with code: PC: Polished Chrome PN: Polished Nickel SN: Satin Nickel ORB: Oil Rubbed Bronze

