# PERLESS

# 6" (152 mm) Φ 6 7/16" (164 mm) 7 13/16" (198 mm) 6 3/16" (157 mm) Φ 2 5/8" (67 mm) 7 1/8" (181 mm) 84" (2134 mm) Φ 3 1/16" (78 mm)

# **Shower Head Spray Patterns**



### **Shower Wand Spray Patterns**





**76465**▲

76465▲ 76465D▲

# SIDEKICK<sup>™</sup> SHOWER SYSTEM

- 2-in-1 Combination Shower
- 3-Spray Setting Shower Head
- 3-Spray Setting Shower Wand

# **FEATURES:**

- Water Amplifying Spray
- Soft Waterfall Spray
- Volume-Adjusting Dial on Shower Wand
- Touch-Clean<sup>®</sup> Nozzles
  Anywhere Mount<sup>™</sup>

# **STANDARD SPECIFICATIONS:**

- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa. (76465▲)
- Maximum 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa. (76465D▲)
- Combination shower with 3 spray setting shower head and 3 spray setting shower wand
- Pause function is a non-positive shut off
- Change shower head spray settings by rotating the diverter lever
- Diverter allows for single or shared operation of shower head (Full body spray only) and shower wand
- 84" (2134 mm) metal hose
- The ball joint swivel angle is 34°(17° per side)
- Fits standard 1/2"-14 NPT pipe fitting

# WARRANTY

 Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.



# **COMPLIES WITH**

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense® Applies to 76465▲ only