

METAL CUTTING JIG SAW BLADES

Shank	TPI	Length	Composition	Pack QTY	Part No.
U-Shank	18	2-3/4"	High Speed Steel	5 Pack	48-42-0120
U-Shank	24	2-3/4"	Bi-Metal	5 Pack	48-42-2160
U-Shank	24	5"	Bi-Metal	5 Pack	48-42-2166
U-Shank	24	2-3/4"	High Speed Steel	5 Pack	48-42-0140

SPECIALTY JIG SAW PRODUCTS

SPECIALTY JIG SAW PRODUCTS

Description	Part No.
2-3/4" Carbide Grit Jig Saw Blade (5 Pk)	48-42-0801
T-Shank Wood and Metal Assortment (5 Pk)	49-22-1178
U-Shank Wood and Metal Assortment (5 Pk)	49-22-1168

Description	Part No.
Anti-Splintering Device	48-08-0530
Plastic Shoe Cover	48-08-0533
Vacuum Manifold and Hose	48-09-1040

MASONRY BITS

HAMMER-DRILL BITS

OVERVIEW

MILWAUKEE® 3-Flat SECURE GRIP™ Hammer-Drill Bits drill faster and last longer than others on the market. The 3-Flat SECURE GRIP™ shank fits in all 1/2" three-jaw hammer-drill chucks and maintains unyielding bit hold with heavy torsional loads. Designed especially for conical anchor, concrete screw, nail-in and hollow wall anchor applications, the bit provides superior performance through its reinforced flute geometry and carbide tip design. MILWAUKEE® offers a complete range of 3-Flat SECURE GRIP™ Hammer-Drill Bits in diameters from 1/8" to 1" with lengths up to 18".

FEATURES

- Reduced Slipping: 3-Flat SECURE GRIP™ shank holds the bit firmly in the chuck
- Longer Life: Carbide tips extend performance in masonry applications



HAMMER-DRILL BITS

Diameter	Usable Length	Length	1 Pack	2 Pack	5 Pack	10 Pack	15 Pack	20 Pack	25 Pack
1/8"	1-1/2"	3"	-	48-20-8800	-	-	-	-	48-20-8900
5/32"	4"	6"	-	48-20-8801	48-20-8955	-	-	-	48-20-8901
3/16"	2"	4"	-	48-20-8805	-	-	-	-	48-20-8905
3/16"	4"	6"	-	48-20-8806	48-20-8957	-	-	-	48-20-8906
1/4"	2"	4"	48-20-8810	-	48-20-8961	-	-	-	48-20-8910
1/4"	4"	6"	48-20-8811	-	48-20-8962	-	-	-	48-20-8911
1/4"	10"	12"	48-20-8812	-	-	-	-	-	-
5/16"	4"	6"	48-20-8816	-	-	-	-	-	48-20-8916
5/16"	10"	12"	48-20-8817	-	-	-	-	-	-
3/8"	4"	6"	48-20-8821	-	-	-	-	48-20-8921	-
3/8"	10"	12"	48-20-8822	-	-	-	-	-	-
3/8"	16"	18"	48-20-8823	-	-	-	-	-	-
7/16"	4"	6"	48-20-8825	-	-	-	-	48-20-8925	-
1/2"	4"	6"	48-20-8830	-	-	-	48-20-8930	-	-
1/2"	10"	12"	48-20-8831	-	-	-	-	-	-
1/2"	16"	18"	48-20-8832	-	-	-	-	-	-
9/16"	4"	6"	48-20-8835	-	-	-	-	-	-
5/8"	4"	6"	48-20-8840	-	-	48-20-8940	-	-	-
5/8"	10"	12"	48-20-8841	-	-	-	-	-	-
5/8"	16"	18"	48-20-8842	-	-	-	-	-	-
3/4"	4"	6"	48-20-8845	-	-	-	-	-	-
3/4"	10"	12"	48-20-8846	-	-	-	-	-	-
7/8"	4"	6"	48-20-8847	-	-	-	-	-	-
7/8"	10"	12"	48-20-8848	-	-	-	-	-	-
1"	4"	6"	48-20-8849	-	-	-	-	-	-
1"	10"	12"	48-20-8854	-	-	-	-	-	-



This product complies with ANSI B212.15 standard