



M12™ FORCE LOGIC™ Press Tool Kit

2473-22 (2473-20 No Jaw Kit)

Specifications:

| | |
|------------------------|----------------------------------|
| Capacity | 1/2" – 1-1/2" Varies by Material |
| Calibration Interval | 32,000 Cycles (LED Indicator) |
| Approximate Cycle Time | 5 Seconds |
| Press Force | 5,400 lbs |
| Length / Weight | 12.8" / 3.8 lbs |

Includes: 2473-22 (3) Jaws (1/2", 3/4", 1"); 2473-20 (No Jaws Included); **All Kits Include:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger, Carrying Case

Related Accessories:

- 49-16-2450 1/2" CTS-V Press Jaw
- 49-16-2451 3/4" CTS-V Press Jaw
- 49-16-2452 1" CTS-V Press Jaw
- 49-16-2453 1-1/4" CTS-V Press Jaw
- 49-16-2450B 1/2" IPS-P Press Jaw
- 49-16-2451B 3/4" IPS-P Press Jaw
- 49-16-2452B 1" IPS-P Press Jaw
- 49-16-2451C 1/2" PEX-Crimp Press Jaw
- 49-16-2453C 3/4" PEX-Crimp Press Jaw
- 49-16-2454C 1" PEX-Crimp Press Jaw
- 49-16-2455C 1-1/4" PEX-Crimp Press Jaw
- 49-16-2456C 1-1/2" PEX-Crimp Press Jaw
- 49-16-2496B 1/2"-1" IPS-P Press Jaw Kit



M12™ M-SPECTOR FLEX™ 9 ft Inspection Camera Cable Kit

2316-21

Specifications:

| | |
|----------------------|--------------------------|
| Screen Size | 3.5" High-Resolution LCD |
| Camera Resolution | 640 x 480 |
| Camera Head Diameter | 12.5 mm (0.49") |
| Cable Length | 9 ft |
| Wireless Distance | Up to 15 ft |

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M12™ M-SPECTOR FLEX™ 3 ft Inspection Camera Cable Kit

2315-21

Specifications:

| | |
|----------------------|--------------------------|
| Screen Size | 3.5" High-Resolution LCD |
| Camera Resolution | 640 x 480 |
| Camera Head Diameter | 12.5 mm (0.49") |
| Cable Length | 3 ft |
| Wireless Distance | Up to 15 ft |

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M-SPECTOR FLEX™ Inspection Camera Accessories

Compatible with 2317-21, 2316-21, 2315-21

- 48-53-0155 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™
- 48-53-0151 M-SPECTOR FLEX™ 9 ft Inspection Camera Cable
- 48-53-0150 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable



M12™ M-SPECTOR 360™ Rotating Inspection Scope Kit

2313-21 (2313-20 Tool-Only)

Specifications:

| | |
|----------------------|--------------------------|
| Screen Size | 2.7" High-Resolution LCD |
| Display Resolution | 320 x 240 |
| Camera Head Diameter | 9 mm (0.35") |
| Cable Length | 3 ft |
| LED Brightness | 4 LEDs, 5 Settings |

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Charger, Contractor Bag



M12™ M-SPECTOR 360™ 9 ft Rotating Inspection Scope Kit

2314-21

Specifications:

| | |
|----------------------|--------------------------|
| Screen Size | 2.7" High-Resolution LCD |
| Display Resolution | 320 x 240 |
| Camera Head Diameter | 9 mm (0.35") |
| Cable Length | 9 ft |
| LED Brightness | 4 LEDs, 5 Settings |

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Pipe Guide, Charger, Contractor Bag



M-SPECTOR 360™ Rotating Inspection Scope Accessories

Compatible with 2313-21, 2314-21

- 48-53-0112 3 Pc Accessory (Includes Hook, Magnet, Mirror Attachments)
- 48-53-0113 Pipe Guide Accessory



M12™ 12:1 Infrared TEMP-GUN™

2278-20 Tool-Only

Specifications:

| | |
|------------------------|---------------------------------|
| Distance-to-Spot Ratio | 12:1 |
| Temperature Range | -22°F – 1,022°F (-30°C – 550°C) |
| Basic Accuracy | +/-1.8% |
| Max/Min/Avg/Dif | Yes |
| High/Low Alerts | Yes |
| Emissivity | Fixed, .95 |
| Drop Test | 6 ft |

Battery and Charger Sold Separately



M12™ Green Laser Kit - 360° 3-Plane

3632-21

Specifications:

| | |
|---------------------|-----------------|
| Range with Detector | 165 ft |
| Working Range | 125 ft |
| Accuracy | +/-1/8" @ 33 ft |
| Self-Leveling | +/-4° Tilt |
| Water & Dust Rating | IP54 |
| Impact Resistant | 1 m |

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Target, Charger, Carrying Case



M12™ Green Laser Kit - Cross Line & Plumb Points

3622-21 (3622-20 Tool-Only)

Specifications:

| | |
|---------------------|-----------------|
| Range with Detector | 165 ft |
| Working Range | 125 ft |
| Accuracy | +/-1/8" @ 33 ft |
| Self-Leveling | +/-4° Tilt |
| Water & Dust Rating | IP54 |
| Impact Resistant | 1 m |

Includes: (1) M12™ REDLITHIUM™ CP3.0 Battery Pack, Target, Charger, Carrying Case



USB Rechargeable Green Laser - Cross Line & Plumb Points

3522-21

Specifications:

| | |
|----------------------|-----------------|
| Ranger with Detector | 165 ft |
| Working Range | 100 ft |
| Accuracy | +/-1/8" @ 33 ft |
| Self-Leveling | +/-4° Tilt |
| Water & Dust Rating | IP54 |
| Impact Resistant | 1 m |

Includes: (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Riser, Carrying Case



USB Rechargeable Green Laser - Cross Line

3521-21

Specifications:

| | |
|----------------------|-----------------|
| Ranger with Detector | 165 ft |
| Working Range | 100 ft |
| Accuracy | +/-1/8" @ 33 ft |
| Self-Leveling | +/-4° Tilt |
| Water & Dust Rating | IP54 |
| Impact Resistant | 1 m |

Includes: (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case



USB Rechargeable Green Laser - 3-Point

3510-21

Specifications:

| | |
|---------------------|-----------------|
| Working Range | 150 ft |
| Accuracy | +/-1/8" @ 33 ft |
| Self-Leveling | +/-4° Tilt |
| Water & Dust Rating | IP54 |
| Impact Resistant | 1 m |

Includes: (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case



Laser Accessories

Compatible with 3632-21, 3622-21, 3522-21, 3521-21, 3510-21

- 48-35-1211 165' Laser Line Detector
- 48-35-1411 72" Laser Tripod
- 48-35-1311 360° Laser Bracket
- 48-35-1111 Responsive Laser Alignment Target
- 48-35-1313 Laser Track Clip

M12™ No-Hub Driver Kit

2455-22 (2455-20 Tool-Only)

Specifications:

| | |
|--------------------------|-------------------------------|
| Torque Settings (3-Mode) | 60 in-lbs / 80 in-lbs / Drill |
| RPM | 0 – 750 |
| Chuck Type | 1/4" Hex |
| Calibration Interval | 25,000 Cycles (LED Indicator) |
| Weight | 2.7 lbs |

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) SHOCKWAVE Impact Duty™ Nut Drivers (1/4", 5/16", 3/8"), Charger, Carrying Case



M12™ M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™ Kit

2317-21

Specifications:

| | |
|----------------------|------------------------------|
| Screen Size | 3.5" High-Resolution LCD |
| Camera Resolution | 640 x 480 |
| Camera Head Diameter | 12.5 mm (0.49") |
| Head Movement | Up to 270° PIVOTVIEW™ Camera |
| Cable Length | 3 ft |
| Wireless Distance | Up to 15 ft |

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M12™ ROCKET™ Dual Power Tower Light

2132-20 Tool-Only

Specifications:

| | |
|--------|---------------------------------------|
| Lumens | 1,400 / 700 |
| Modes | High, Low |
| Height | 30.5" Collapsed, 5' 8" Fully Extended |
| Weight | 6.7 lbs |

Battery and Charger Sold Separately

