

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 3.5 gpf (13.2 Lpf) (3.5)

Water Efficiency

Water Saver Low Consumption

Push Button

Metal Button Panel Mount (MBPM)

Adapter

XL Sweat Solder Adapter Kit (XL)

Compliances & Certifications

BAA Compliant UPC Certified cUPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

Regal® Concealed Manual Specialty Water Closet Hydraulic Flushometer

FEATURES

- Royal®, Regal® and Sloan® Prison Flushometers feature all the performance benefits of standard concealed, diaphragm model Flushometers with added durability to withstand rough environments
- Flush volumes as low as 0.5 gpf/1.9 Lpf meet waterefficiency goals
- Choose from Flushometers intended for use with stainlesssteel urinal fixtures from various manufacturers
- Choose from Flushometers intended for use with stainlesssteel urinal fixtures from various manufacturers
- Diaphragm, handle packing, stop seat and vacuum breaker molded from PERMEX® rubber compound for chloramine resistance
- Vandal-proof, push button operation with ADA-compliant fixture wall or panel-mount actuator options on select models
- Non-hold-open feature keeps fixture from surpassing intended water consumption
- Adjustable tailpiece accommodates various installations
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

 Concealed Flushometer Installation Instructions for Stainless Steel Fixtures

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com





- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Regal Flushometers Repair and Maintenance Guide
- Hydraulic Push Button Options
- Additional Downloads