


ewable Energy



Slimline[®] Bedpan BPW-9000 Washer Model Hydraulic Flushometer

Description

Royal[®] Slimline[®] Bedpan Washer Water Closet Hydraulic Flushometer, for floor mounted or wall hung top spud bowls.

Flush Cycle

□ Model BPW-9000-1.6 Low Consumption (1.6 gpf/6.0 Lpf) □ Model BPW-9000 Water Saver (3.5 gpf/13.2 Lpf)

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Hydraulic Actuated Closet Flushometer with the following features:

- Dual Filtered Bypass
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Free Spinning Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with Onepiece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 11/2" Top Spud
- Sweat Solder Adapter w/Cover Tube & Cast Wall Flange w/Set Screw
- Diaphragm, Stop Seat and Vacuum Breaker molded from PERMEX™ rubber compound for Chloramine resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources – Wind Energy

Bedpan Washer Diverter Assembly with the following features:

- Solid One-piece Body Construction
- Solid Brass Spray Arm
- Counter Balanced Pivot Assembly
- Diverter Valve Wall Support

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037 and ANSI/ASME A112.19.2.

- Actuator Types: (please check one)
 - **FW** Standard Fixture Wall Actuator (HY-33-A)
 - □ MP Metal Partition Actuator (HY-49-A)
 - Side Wall Mounted Actuator (HY-72-A)
 - □ MBFW Metal Button Fixture Wall Actuator (HY-100-A)

See Hydraulic Flushometer Section of the Sloan catalog for additional information on Hydraulic Valves and Actuators.

Variations

- Two Wall Bumpers (for open front seat without cover)
- SaniGuard[®] Antimicrobial Spray Arm

Listed by I.A.P.M.O.



This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.



Made in the U.S.A. SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Phone: 1-800-982-5839 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com

Slimline BPW-9000 S.S. — Rev. 0a (03/09) Copyright © 2009 SLOAN VALVE COMPANY