


Min. 2 1/2" (64 mm) Clearance To Back Splash 6" to 16" 152 mm to 406 mm) 9 1/4" (235 mm) Centers 16 1/8" (410 mm) 2X 1 7/8" 2 3/16" (56 mm) Dia. (48 mm) 3" (76 mm) Max. Deck Thickness Dia. 9 1/8' (232 mm) - 3x 1 1/8" to 1 1/2" (29 mm to 38 mm) Hole Size 7 1/2" (190 mm) 1/2 14NPSM



▲ Designate Proper Finish Suffix

BRIZO

KITCHEN FAUCET

- Kintsu® Bath Collection
- Two Handle Widespread Pull-Down

FEATURES:

- MagneDock® Magnetic Docking
- Touch-Clean® Spray Holes
- Lumicoat[™] Finish (-L models only)
- Lumicoat[™] Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Max flow rate 1.8 gpm @ 60 psi, 6.8 L/min @ 414 kP
- Three hole mount
- Spout rotates 360°
- Ceramic cartridge
- 1/2-14 NPSM threaded inlets
- · Quick connect hoses
- Two-function wand: Aerated stream or spray
- Dual integral check valves in sprayer
- Handles sold separately. See handle options below
- Note: Optional red/blue temperature indicator rings, order RP101685

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts and Batteries (if applicable) 5 years from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, 1 year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.). No warranty is provided on batteries.
- Please go to www.brizo.com for the complete details of our limited warranty.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A 112.18.6
- Indicates compliance to ICC/ANSI A117.1