

TUBING



3808/3810

NuTone's semi-rigid white PVC tubing has exceptional tensile strength. Lightweight and easy to handle, it can be cut with an ordinary saw. Its self-extinguishing properties will not support combustion making it extremely safe for your home's walls. Installs vertically or horizontally and is not affected by weather – won't rust or deteriorate.

- Conforms to all UL requirements
- Manufactured in conformity with ASTM F2158 and UMC certified
- 2" OD x 8' or 10' lengths

TUBING GUIDE

Number of Inlets	3	4	5	6	7
PVC Tubing Required	48'	64'	80'	100'	120'

Fittings, tubing and installation kits to meet every installation need – all from one source... NuTone.

Bulk packs available! Please check NuTone price sheet or packaging information.

FITTINGS

CI3301RK Rough In

for 1-inlet installation includes:

- | | |
|------------------------------|--------------------|
| 1 – Mounting Bracket | 1 – 45° Street Ell |
| 1 – Plaster Guard | 2 – Nail Guards |
| 2 – Screws for Plaster Guard | 2 – 90° Sweep Ells |
| 1 – 90° Elbow | 1 – 45° Ell |
| 1 – 90° Street Ell | 1 – 90° Tee Wye |
| | 2 – Stop Couplings |

CI3303RK Rough In

for 3-inlet installation includes:

- | | |
|------------------------------|-----------------------|
| 3 – Mounting Brackets | 6 – Nail Guards |
| 3 – Plaster Guards | 6 – 90° Sweep Ells |
| 6 – Screws for Plaster Guard | 2 – 45° Ells |
| 3 – 90° Elbows | 3 – 90° Tee Wyes |
| 1 – 90° Street Ell | 6 – Stop Couplings |
| 1 – 45° Street Ell | 1 – Solvent Cement |
| | 1 – 1001 18/2 UL Wire |