


▲ Designate proper finish suffix





see what Delta can do

H₂OKINETIC® HAND SHOWER

■ 3-Spray Setting Hand Shower

FEATURES:

- Touch-Clean[®] Spray Holes
 H₂Okinetic[®] Technology
 Lumicoat[®] Finish (-PR models only)
- Lumicoat[®] Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- · Certified dual check valves for backflow protection
- Change spray modes with pushbutton
- Hand held shower with three spray settings pause is a non-positive shut-off
- 60"- 82"(1524 mm-2083 mm) stretchable metal hose
- 24" (610 mm) wall bar with adjustable slide (51799-▲ & 51799-▲-PR only)
- Wall mount bracket for hands-free showering (55799-▲-PR
- Lumicoat $^{\mathbb{R}}$ is not applied to the slide bar or shower hose
- 3 Spray settings include: H₂OKinetic[®] spray, Massaging spray and Pause

WARRANTY:

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1◆
- ASME A112.18.3
- EPA WaterSense[®]
- ◆Your Delta hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two contributes the control of the contro certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2025 Delta Faucet Company