

see what Delta can do™

IN2ITION®

- 2-In-1 Shower
- 4-Spray Setting Hand Shower

FEATURES:


- Touch-Clean® Spray Holes

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Shower with four spray settings - pause is a non-positive shut-off
- Adjustable shower arm mounting hands-free showering
- Diverter allows for single or shared operation of the shower head and hand shower
- Ball connector swivel angle is 22° (11° per side)
- Easy turn dial to change sprays
- 6" fixed shower head with extra-wide spray
- 60" (1524 mm) stainless steel hose (Chrome, SN finishes)
- 60" (1524 mm) UltraFlex® hose (RB, BL finishes)
- 4 Spray settings include: Full Body spray, Full Spray with Massage, Massaging spray and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



▲ Designate proper finish suffix



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-75486C Rev. E

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company