

NEW Ultra Thin Cut Off Wheels

FASTER CUTTING 20% Thinner Than Most Competitor Wheels.

Zirconia Aluminum construction makes these wheels ideal for ferrous metals including stainless steel

Ultra thin design requires less energy for improved battery life when used with cordless grinders

60 grit abrasive for cleaner cuts



SPEED



.032" thick for faster cutting and reduced material waste

Ultra Thin Cut-Off Wheels

Diameter	Thickness	Arbor Hole	Grit	Max Safe RPM	Model	1/Pkg. Part #	25/Pkg. Part #
4"	.032"	5/8"	60	15,300	GA4030	B-46143	B-46143-25
4-1/2"	.032"	7/8"	60	13,300	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	B-46159	B-46159-25
5"	.032"	7/8"	60	12,250	9005B/BZ, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y	B-46165	B-46165-25



- .032" thick for faster cutting and reduced material waste
- For making cuts in metal and stainless steel pipes, sheet, and channel

C

Flex & Cut-Off Wheels

14 Super Thin Cut-Off Wheels

Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	Model	Stainless 25/Pkg. Part #	Metal 25/Pkg. Part #
4"	3/64" / .045"	5/8"	46	15,280	GA4030	724111-A-25	724114-A-25
4-1/2"	3/64" / .045"	7/8"	46	13,285	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	724112-A-25	724115-A-25
5"	3/64" / .045"	7/8"	46	12,200	9005B/BZ, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y	724113-A-25	724116-A-25
6"	1/16" / .060"	7/8"	46	10,185	9566CV/PC, GA6010Z, GA6020	724118-A-25	724117-A-25



- Super thin design lasts up to 3.5x longer than standard cut-off wheels
- Engineered for less heat discoloration, less material removal and less burring for a better finish

13 Cut-Off Wheels

Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	Model	Bulk Shelf Pack Qty.	Metal Bulk * Part #	Metal 10/Pkg. Part #	Masonry 10/Pkg. Part #
4"	3/32" / .090"	5/8"	36	13,600	GA4030	25	A-90358 (*Must be ordered in shelf pack quantity)		
4"	5/64" / .080"	5/8"	46	14,000			724107-5-10		
4"	3/32" / .090"	5/8"	36	15,000			724104-1-10		



- For all ferrous materials, steel and cast iron
- For masonry/concrete, marble, slate and more

12 Flex Wheels

Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	Model	10/Pkg. Part #
4"	1/8"	5/8"	46	13,700	GA4030	741404-OBP*
4"	1/8"	5/8"	60	13,700		741404-0CP*



- Most versatile wheel for light metal grinding, sanding and cutting

*Use with Plastic Back-up Pad *743009-1A

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.