



## GA5040X1

### 5" SJS™ II ANGLE GRINDER WITH TUCK POINT GUARD

#### 5" Dust Extraction Tuck Point Guard and Diamond Blade

- Powerful 10.0 AMP motor delivers more output and 11,000 RPM
- SJS™ II provides a leaf spring and cam gear drive mechanism that is engineered to reduce vibration for increased operator comfort during extended use
- Includes 5" dust extraction tuck point guard for clean and accurate tuck pointing and cutting
- Labyrinth construction seals and protects the motor and bearings from dust and debris for longer tool life

**Model GA5040X1 Includes:** 5" Dust Extracting Tuck Point Guard (196845-3), Inner Flange (224399-1), Lock Nut Wrench (782412-6), 5" Dual Sandwich Diamond Tuck Point Blade (A-96017), 5" Tool-less Wheel Guard (123145-8), Side Handle (162258-0)

Wheel Diameter	5"
AMPS	10
No Load Speed	11,000 RPM
Spindle Thread	5/8" - 11 UNC
Lock-On: Yes	Lock-Off: No
Grinder Switch Type	Body grip/slide
Overall Length	11-7/8"
Net Weight	5.4 lbs.
Shipping Weight	12 lbs.



## GA5042CX1

12 AMP

### 5" SJS™ II HIGH-POWER GRINDER WITH TUCK POINT GUARD

#### 5" Dust Extraction Tuck Point Guard and Diamond Blade

- Powerful 12.0 AMP motor delivers more output and variable (2,800 - 11,000) RPM
- SJS™ II provides a leaf spring and cam gear drive mechanism that is engineered to reduce vibration for increased operator comfort during extended use
- Includes a 5" dust extraction tuck point guard for clean and accurate tuck pointing and cutting

**Model GA5042CX1 Includes:** 5" Dust Extracting Tuck Point Guard (196845-3), Inner Flange (224399-1), Lock Nut Wrench (782412-6), 5" Dual Sandwich Diamond Tuck Point Blade (A-96017), 5" Tool-less Wheel Guard (123145-8), Lock Nut (224568-4)

Wheel Diameter	5"
AMPS	12
No Load Speed (variable speed)	2,800 - 11,000 RPM
Spindle Thread	5/8" - 11 UNC
Lock-On: Yes	Lock-Off: No
Grinder Switch Type	Body grip/slide
Overall Length	11-7/8"
Net Weight	5.4 lbs.
Shipping Weight	13 lbs.



## PC5001C

### 5" CONCRETE PLANER

#### Adjustable Front Roller for Consistent Planing Depth

- Powerful 10.0 AMP motor delivers more output and 10,500 RPM
- Constant Speed Control automatically applies additional power to the motor
- Soft start suppresses start-up reaction for more control and longer tool life
- Electronic current limiter helps protect the motor from overload
- Anti-restart prevents accidental start up after power loss

**Model PC5001C Includes:** 5" Diamond Cup Wheel, Continuous Rim (A-94998), Hex Wrench (783203-8), Lock Nut Wrench (782425-7), Dust Bag (122853-8), Brush Set (194921-7), Steel Tool Case

Wheel Diameter	5"
No Load Speed	10,000 RPM
AMPS	10
Overall Length	18-13/16"
Net Weight	11.2 lbs.
Shipping Weight	26.5 lbs.



## 4101RH

### 5" MASONRY SAW

#### For Wet Cutting of Tile, Masonry, Concrete and More

- Powerful 7.9 AMP motor for the most demanding jobs
- Special cover design prevents water from entering into motor housing
- Cuts up to 1-5/8" at 90° and 1" at 45°
- Ground fault circuit interrupter (GFCI) plug
- Lock-on button for continuous operation
- Includes 15 ft. of tubing, water pressure regulator and water valve

**Model 4101RH Includes:** 5" Diamond Blade, Continuous Rim, Wet Cutting (A-90934), Hex Wrench (783203-8), Spanner Wrench (781011-1)

Blade Diameter	5"
Arbor	3/4"
Max Cutting Capacities:	at 90° (1-5/8"), at 45° (1")
No Load Speed	13,800 RPM
Watts Out	1,050
AMPS	7.9
Overall Length	9-1/4"
Net Weight	6.5 lbs.
Shipping Weight	9.3 lbs.



## 4100NH

### 4-3/8" MASONRY SAW

#### Powerful Cutting in Stone, Masonry, Tile & Concrete

- Powerful 12 AMP motor
- Cuts up to 1-3/8"
- Compact and lightweight at only 6.5 lbs.
- High power to weight ratio; 14,500 RPM
- Lock-off button helps prevent accidental starts
- Flat rear side of motor housing allows for easy blade changes

**Model 4100NH Includes:** Socket Wrench (782209-3), Spanner Wrench (781011-1), 4" Diamond Blade, Turbo, General Purpose (A-94546)

Blade Diameter	4-3/8"
Arbor	3/4"
Max Cutting Capacity	at 90° (1-3/8")
No Load Speed	14,500 RPM
Watts Out	1,500
AMPS	12
Overall Length	8-5/8"
Net Weight	6.5 lbs.
Shipping Weight	9.46 lbs.

# SMOOTH OPERATOR



## Concrete Planer Accessories

### Diamond Cup Wheels

Size	Description	Model	Part #
5"	Segmented rim for fast material removal	PC5000C, PC5001C	A-95009
5"	Continuous Rim For a smooth finish		A-94998
4-3/8"	Continuous rim for a smooth finish	PC1100	792289-1
4-3/8"	Segmented for fast material removal		724907-1A

## PC5000C

### 5" CONCRETE PLANER

#### Electronic Controller for Operator Convenience

- Powerful 10 AMP motor delivers more output and 10,500 RPM
- Constant Speed Control automatically applies additional power to the motor
- Soft start suppresses start-up reaction for more precision and longer tool life
- Electronic current limiter helps protect the motor from overload
- Anti-restart prevents accidental start up after power loss
- Large two-finger trigger switch with lock-on for continuous operation

**Model PC5000C Includes:** 5" Diamond Cup Wheel, Segmented Rim (A-95009), Lock Nut Wrench (782425-7), Hex Wrench (783203-8), Dust Bag (122853-8), Brush Set (194921-7), Steel Tool Case

Wheel Diameter	5"
No Load Speed	10,000 RPM
AMPS	10
Overall Length	17-1/8"
Net Weight	8.9 lbs.
Shipping Weight	8.9 lbs.

## Diamond Blades

### Segmented Rim

Segment slots help deliver a faster cooler cut in multiple applications

Blade Diameter	Material	Part #
4"	Cured Concrete, Block, Brick	A-94677
5"	Cured Concrete, Block, Brick	A-94699

### Turbo Rim

Constant contact with material delivers a smoother finish than segmented blades

Blade Diameter	Material	Part #
4"	Cured Concrete, Block, Brick	A-94546
4"	Granite, Ceramic, Fire Brick	A-94580
5"	Cured Concrete, Block, Brick	A-94568
5"	Granite, Ceramic, Fire Brick	A-94605

### Continuous Rim

Blade Diameter	Material	Part #
5"	Cured Concrete, Block, Brick	A-90934

**Additional Diamond Blades See pg. 105**