Tapping Tools



75982

Cutters

Catalog No.	Model No.	Diameter in	Туре	
52760	M16	5⁄8		
52780	M22	7⁄8		
52800	M29	1 1/8	Bi-Metal	
52820	M35	1 3⁄8		
52850	M44	1 3/4		
76267		5⁄8	Steel	
76272		7⁄8	Shell	
76292		5⁄8	CI/DI D:+	
76297		7/8	CI/DI Bit	
76317	-	5⁄8	Plastic	
76322		7⁄8	Shell	
76277		1 ½	0	
76282		1 3/8	Steel Shell	
76287		1 ¾	Onon	
76302		1 ½	CI/DI Shell	
76307		1 3/8		
76312		1 ¾		
76327		1 ½		
76332	-	1 3/8	Plastic Shell	
76337		1 3/4		

Note: Cutter diameter is $^1/8$ - $^1/4^{\prime\prime}$ smaller than the diameter of the hole being cut.

Pilots

Catalog No.	Description
76027	Coupon Retaining ¼" Pilot
76032	Coupon Retaining 3/8" Pilot

Hole Saw Arbors

Catalog No.	Description	
76037	Small Arbor for 5/8" - 1 3/16" Hole Saws	
76042	Large Arbor for 1 5/16" - 1 3/4" Hole Saws	

Shaft Extensions

Catalog No.	Description	
76047	Small Shaft Extension for 5/8" - 1 3/16" Hole Saws	
76052	Large Shaft Extension for 1 5/16" - 1 3/4" Hole Saws	

RT3422 TAPPING TOOL

RT3422 is designed for branching pressurized water, steam and natural gas mains. With up to 2" capacity, corrosion-proof design, ability to handle most types of material and lightweight, the Model RT3422 is the tool to meet your tapping needs.

- Easy to use. At only 21", this lightweight and compact tool is great for tight quarters and awkward locations.
- · Heavy-duty design. Sturdy machined, corrosion-resistant materials for dependable lifelong benefits.
- Built-in bleed valve allows for easy purge of chips.
- Independent cutter feed gives the operator total independent control of the cutter feed rotation for optimal saw life.
- Taps a variety of materials including steel, cast iron, ductile iron and plastic pipe.
- Versatility. RT3422 is capable of tapping mains of water up to 500 psig and steam, air and natural gas up to 150 psig.
- Coupon retaining bits. Exclusive pilot bits give you the confidence that the coupon will not be dropped in the pipe, preventing medium contamination or possible damage of downstream equipment.

SPECIFICATIONS

- Tapping Capacity 3/4" 2"
- Mounting Saddle, welded nipple, Weldolet®, Threadolet®
- Cutter Travel 14"
- Activation Hand ratchet, air ratchet, right angle drill
- Cutter Feed Rotation of sleeve around an Acme threaded barrel
- Pressure Water: 500 psig @ 100°F
- Steam, air and natural gas, 150 psig @ 370°F

Catalog No	Model No.	Description	Weight	
Catalog No.	Model No. Description		lb	kg
75982		Tapping Machine Only	16	7.3
75992	RT3422	¾" - 2" NPT Set (Male)	5.3	13.6
91192		¾" - 2" CTS Set (Flared)	4 4/5	3

Accessories

Catalog No.	Description
76022	11/16" Ratchet Wrench
76017	RT 3422 Tool Box

Valve Adapters

•	
Catalog No.	Description
76057	CTS ¾" Female Adapter
76067	CTS 1" Female Adapter
76072	CTS 1 ¼" Female Adapter
76077	CTS 1 ½" Female Adapter
76082	CTS 2" Female Adapter
76132	NPT ¾" Male
76137	NPT 1" Male
76142	NPT 1¼" Male
76147	NPT 1 ½" Male
76152	NPT 2" Male
83997	¾" Mueller 110
84002	1" Mueller 110
84007	1 ½" Mueller 110
84012	2" Mueller 110

NPT Sets available only with steel, male valve adapters.

Standard Equipment

Catalog No.	Description	75982 RT3422	75992 RT3422	91192 RT3422
76022	11/16" Ratchet Wrench		•	•
76047	Small Shaft Extension for 5/8" - 1 3/16" Hole Saws		•	•
76037	Small Arbor for 5/8" - 1 3/16" Hole Saws		•	•
76052	Large Shaft Extension for 1 5/16" - 1 3/4" Hole Saws		•	•
76042	Large Arbor for 1 ⁵ / ₁₆ " - 1 ¾" Hole Saws		•	•
34100	Spud Wrench (2)		•	•
76132	NPT ¾" Male		•	
76137	NPT 1" Male		•	
76142	NPT 1 1/4" Male		•	
76147	NPT 1 ½" Male		•	
76152	NPT 2" Male		•	
76057	CTS ¾" Female Valve Adapter			•
76067	CTS 1" Female Valve Adapter			•
76072	CTS 1 1/4" Female Valve Adapter			•
76077	CTS 1 ½" Female Valve Adapter			•
76082	CTS 2" Female Valve Adapter			•
76027	Coupon Retaining ¼" Pilot		•	•
76032	Coupon Retaining 3/8" Pilot		•	•