



## XP-300 SERIES

Versatility and power are the hallmarks of this longer radius Stream Rotor which offers a choice of four nozzles, 11 interchangeable arc discs and a 28' - 43' radius. Adjustment screw allows up to 25% radius reduction on two main streams.

### LAWN POP-UP

- Radius: 28' - 43' (8,8 - 13 m)
- Flow Rate: 1.01 - 10.81 GPM (3,82 - 41 LPM)
- Pop-Up to Nozzle: 3 3/4" (95mm)
- Height: 6 1/8" (157mm)

### HIGH-POP

- Pop-Up to Nozzle: 12 1/2" (313mm)
- Dimensions: Body diameter - 2 7/8" (72mm) Height - 16" (405mm)

### SHRUB

- Flow Rate (COM): 3.25 - 10.52 GPM (12,5 - 38,3 LPM) (360° arc disc)
- Check Valve: Optional
- Base Diameter: 1 3/4" (45mm)

### Specifying Information

XP XX XX XX COM E

Arc	Body	Nozzle	Optional	Optional
04-90°	S- Shrub	05-(For service only order 35-5460)	COM-Check-O-Matic*	E-Effluent
05-115°	P- Lawn	07		
06-140°	Pop-up	09		
07-165°	HP-High-Pop**	10		
08-180°				
09-190°				
10-210°				
12-225°				
13-270°				
14-360°				

Example: A 300 Series Shrub Sprinkler with a 90° arc and an adjustable nozzle would be specified as: **304-10-15**

\*Available with shrub models only  
\*\*Models use high-pop nozzles with collar. (Order Part No. 35-5460 and 35-2049)

### XP-300 HIGH-POP NOZZLE & COLLAR ASSEMBLY

A spacing collar must be used on the high-pop to ensure proper sealing and retraction.



Exclusive arc discs and rotating nozzle control the pattern of water and rate of distribution to provide matched precipitation rates.

**TORO**

Count on it.

RESIDENTIAL & COMMERCIAL

# Stream Rotor® Series

300 Series 340 Series XP-300 Series  
Rotary Sprinklers

Toro multi-stream sprinklers provide acclaimed reliability and superior performance, making it the ideal choice for residential and light commercial applications. With extremely precise precipitation rates, Toro's stream rotor series provide uniform coverage across your lawn or planted areas.



### UNIQUE

"Fingers of Water" provide gentle, slow and effective watering and visual appeal. The matched precipitation rates on nozzles ensure uniform water coverage across your lawn.

### VERSATILE

Interchangeable arc plates and nozzles provide the ultimate in versatility and the ability to cover varying arc requirements. A wide selection of body styles – pop, shrub, and high-pop – satisfy a variety of installation requirements (such as slopes with shrub sprinklers).

### RELIABLE

Effluent and check valve options for some models offer safety in reclaimed water situations and to prevent low head drainage. Durable engineering plastic and stainless steel construction. Two-year warranty.

www.toro.com

The Toro Company • Irrigation Division  
An ISO 9001 Certified Facility • PO Box 489 • Riverside, CA • 92502 • 800.664.4740  
490-3094 Specifications subject to change without notice. For more information, contact your local Toro distributor. ©2006 The Toro Company. All rights reserved.

**TORO**



**OPERATIONAL FEATURES**

- Large basket filter screen to prevent clogging
- Recycled water indicators available
- Locking cap available for lawn pop-up models (Part no. 35-1344, standard on high-pop models)

**COMMON SPECIFICATIONS - All Models**

**Lawn Pop-Up**

- Recommended operating pressure: 35-50 psi (2,4 - 3,5 Bar)
- Maximum operating pressure: 75 psi (5,2 Bar)
- Body Diameter: 2 3/8" (59mm)
- Cap Diameter: 3" (75mm)
- 3/4" (20mm) female-threaded inlet

**High-Pop**

- 3/4" (20mm) female-threaded bottom and side inlets
- Side inlet: 7" (175mm) from top of sprinkler to center of side inlet
- Cap diameter: 3" (75mm)

**Shrub**

- 1/2" to 3/4" (13 - 20mm) female-threaded inlet
- Optional check valve maintains up to 8' (2,4m) elevation change

**MATCHED PRECIPITATION. MATCHED PERFORMANCE**

Matched Precipitation Rate (MPR) ensures uniform delivery of water across each square foot of an irrigated area.

Each sprinkler's coverage provides every blade of grass with no more – and no less – water than the next.

The result is high-precision water application and consistently green, healthy grass.



340 Series Arc Disc Tree

A wide range of interchangeable matched precipitation Arc Discs let you select various angles of coverage from 90° to 360°.



Uniquely designed, stream rotors feature multiple rotating streams. These graceful "fingers of water" create a striking visual effect that never fails to turn heads. Plus, you can zone your sprinklers together, saving time and water.



**300 SERIES**

Utilizing gentle water distribution, this rotor provides coverage ideal for medium to large lawns and ground cover. Choice of six nozzles and nine interchangeable arc discs for varying landscape needs.

**LAWN POP-UP**

- Radius: 15' - 30' (4,6 - 9,2 m)
- Flow Rate: 0.57 - 7.51 GPM (2,5 - 28 LPM)
- Pop-Up to Nozzle: 2 3/4" (70mm)
- Height: 6 1/8" (157mm)

**HIGH-POP**

- Pop-Up to Nozzle: 11 3/4" (290mm)
- Dimensions: Body diameter - 2 3/8" (59mm) Height - 16" (405mm)

**SHRUB**

- Flow Rate (COM): 2.07 - 6.36 GPM (7,9 - 23,8 LPM) (360° arc disc)
- Base Diameter: 1 3/4" (45mm)

Specifying Information

Arc	Body	Nozzle	Optional	Optional
04-90° 05-112° 06-135° 07-157,5° 08-180° 09-202,5° 10-225° 12-270° 16-360°	00-Lawn Pop-Up 10-Shrub 12-High-Pop	01-Small Radius, 12 Ports 02-Medium Radius, 12 Ports 03-Large Radius, 12 Ports 15-Adjustable Shrub & Lawn Pop-up 21-Small Radius, 12 Ports, High-pop 22-Medium Radius, 12 Ports, High-pop 23-Large Radius, 12 Ports, High-pop 25-Adjustable High-pop 63-Large Radius, 6 Ports, Low GPM** 93-Large Radius, 9 Ports, Low GPM**	COM-Check-O-Matic*	E-Effluent

Example: A 300 Series Shrub Sprinkler with a 90° arc and an adjustable nozzle would be specified as: **304-10-15**

\*Available with shrub models only  
\*\*Not available in high-pop models



**340 SERIES**

Providing the same gentle water distribution features of the 300 Series, this rotor also provides a longer radius, a higher pop-up, and a standard check valve in the lawn pop-up. Choice of six nozzles and nine interchangeable arc discs for varying landscape needs. One arc tree is supplied for each rotor in the case.

**LAWN POP-UP**

- Radius: 15' - 33' (4,6 - 10 m)
- Flow Rate: 0.57 - 7.54 GPM (2,5 - 28,5 LPM)
- Check Valve: Standard
- Pop-Up to Nozzle: 3 3/4" (95mm)
- Height: 7" (180mm)

**HIGH-POP**

- Pop-Up to Nozzle: 11 3/4" (290mm)
- Dimensions: Body diameter - 2 7/8" (72mm) Height - 16" (405mm)

**SHRUB**

- Flow Rate (COM): 2.07 - 6.36 GPM (7,9 - 23,8 LPM) (360° arc disc)
- Check Valve: Optional
- Base Diameter: 1 3/4" (45mm)

Specifying Information

Arc	Body	Nozzle	Optional	Optional
04-90° 05-112,5° 06-135° 07-157,5° 08-180° 09-202,5° 10-225° 12-270° 16-360°	00-Lawn Pop-Up 10-Shrub 12-High-Pop	01-Small Radius, 12 Ports 02-Medium Radius, 12 Ports 03-Large Radius, 12 Ports 15-Adjustable (Omni) Shrub & Lawn Pop-up 21-Small Radius, 12 Ports, High-pop 22-Medium Radius, 12 Ports, High-pop 23-Large Radius, 12 Ports, High-pop 25-Adjustable (Omni) Nozzle, High-pop 63-Large Radius, 6 Ports, Low GPM** 93-Large Radius, 9 Ports, Low GPM**	COM-Check-O-Matic*	E-Effluent

Example: A 300 Series Shrub Sprinkler with a 90° arc and an adjustable nozzle would be specified as: **304-10-15**

\*Available with shrub models only  
\*\*Not available in high-pop models